




RKDOORSYSTEMS

ekey Home App Instructions






ID 173/324: Version 2, 18.12.2013

Step	Action	Display
3.	No action required.	 The status LED on the finger scanner lights up orange, the function LEDs flash green: default setting.
4.	If the LEDs fail to light up, check the wiring and power supply.	-

Implementation via a smartphone

Implementing the devices allows to couple the ekey home finger scanner integra 2.0 Bluetooth with the smartphone. The following steps apply to the ekey home CP mini 1 only. These steps are carried out automatically for the ekey home CP micro 1.




Implementing the devices

Step	Action	Description	Display
1.		Press and hold the button with the operating rod for 1 sec.	 The upper status LED flashes green.
2nd	No action required.	-	 Status LED lights up orange, the function LEDs flash green.

The system is ready to couple the finger scanner with the smartphone.

The coupling sets the system up programming and administration. You need security codes for the coupling. The default **coupling code** and **app security code** is **9999**.

Coupling the smartphone and setting up the normal mode

Step	Action	Description	Display
1.		Download and install the <i>ekey home app</i> on your smartphone.	 Status LED lights up orange, the function LEDs flash green.
2nd	According to instructions on the display	Couple the smartphone with the finger scanner.	 Status LED lights up blue.

The coupling of the finger scanner with the smartphone has been carried out. The system is in normal mode. You can now start programming and administrating the finger scan access system with your smartphone.

NOTICE IN CASE OF LOSS



Reset your ekey access system, in order to delete the coupling between the smartphone and the ekey access system. Be sure to set a new security code after having reset the system!



RKDOORSYSTEMS

ekey home FS IN 2.0 BT ekey home app

General



The *ekey home finger scanner integra 2.0 Bluetooth* can be set up with a smartphone via *ekey home app*. To do so, follow the operating instructions below.



NOTICE – IMPLEMENTATION WITHOUT A SMARTPHONE

If you wish to implement the system without a smartphone, you should use the printed operating instructions provided with the finger scanner.

Downloading the app

The app can be found on Google Play. Enter the search term “ekey home app”, ideally with quotation marks, or scan the QR code with your smartphone, to get directly to the download.



NOTICE

The *ekey home app* can be used with the following control panels:

- ekey home control panel micro 1*
- ekey home control panel mini 1*
- ekey home control panel integra 1/2* from Q1/2014
- ekey home control panel wall-mounted 1/3* from Q2/2014



RKDOORSYSTEMS

Installation



ATTENTION


Mount and cable the product correctly before connecting power.
Possible property damage!
Do not connect the power supply beforehand!



Mount the system in accordance with the supplied mounting instructions.



Cable the system in accordance with the supplied wiring diagram.

Step	Action	Display
1.	Ensure safe installation of the devices. Close the covers.	-
2.	Connect the power supply to the mains.	 Only for ekey home CP mini 1: The upper status LED on the control panel flashes red: default setting.